


KALU

wall and ceiling light, four-headed, LED, 3000K, square, black, $60^{\circ}\,$

As one would expect, the LED extension of the popular KALU series guarantees the utterly free adjustment of lamp heads. Fitted with dimmable, high output LEDs, the KALU series has just become even more efficient and versatile! Available in matt black or black and white, KALU wall and ceiling light is supplied ready for direct connection to 230V mains supply.



TECHNICAL DATA

Item no.:	1000135		
Lamps included	0		
Primary nominal voltage	220-240V ~50/60Hz mA/V		
Secondary power / secondary voltage	700 mA/V		
Vertical tilting range	120 °		
Horizontal rotation range	340 °		
Length	28.0 cm		
Width	29.0 cm		
Height	16.0 cm		
Net weight	3.75 kg		
Gross weight	4.522 kg		
IP Code	IP 20		
Safety class	I		
Assembly	Surface		
Assembly details	Ceiling,Wall		
Dimming technology	trailing edge		
Wattage	60 W		
Lumen	4000 lm		
Colour temperature	3000 Kelvin		
Beam angle	60 °		
Color	black		
CRI	>80		
	!		





Binning	6
LXXBXX data	70/50
Service life	40000 h
BIG WHITE Page	353

Notes			