



## PANEL 60 round

**LED Indoor surface-mounted ceiling light, white, 4000K**

The LED PANEL 60 comes with several different light and housing colours, and provides a modern and space-saving solution for an efficient type of basic lighting. The high degree of luminous flux provides a pleasant, homogeneous and glare-free lighting feeling. The electrical connection is made directly to the 230V mains voltage supply. This luminaire contains built-in LED lamps.

### TECHNICAL DATA

Item no.:	1000784
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	1000 mA/V
Height	5.5 cm
Diameter	60.0 cm
Installation diameter	20.0 cm
Installation depth	7.0 cm
Net weight	4.628 kg
Gross weight	5.4 kg
IP Code	IP 20
Safety class	I
Assembly	Surface
Assembly details	Ceiling
Dimming technology	trailing edge
Number of through-wires	40
Wattage	42 W
Lumen	3350 lm
Colour temperature	4000 Kelvin
Beam angle	110 °
Color	white
CRI	>80
UGR ≤	22



<b>Binning</b>	6
<b>LXXBXX data</b>	70/50
<b>Service life</b>	30000 h
<b>BIG WHITE Page</b>	304

**Notes**

---

---

---

---

---