




L-LINE 120 LED

wall and ceiling light, IP44, 3000K, 3000lm, grey

The L-LINE 120 wall and ceiling light, which is equipped with a warm-white LED module, is the ultimate LED solution for primary room illumination thanks to the LED output. The sleek and elegant L-LINE 120 is available in white, silver-grey and grey. Thanks to the integrated LED driver, the luminaire can be connected directly to a 230 Volt mains power supply.



TECHNICAL DATA

Item no.:	1001305
Lamps included	0
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	350 mA/V
Width	117.8 cm
Height	7.0 cm
Depth	7.0 cm
Net weight	2.186 kg
Gross weight	2.573 kg
IP Code	IP 44
Safety class	I
Assembly	Surface
Assembly details	Wall
Wattage	18.5 W
Lumen	1650 lm
Colour temperature	3000 Kelvin
Beam angle	120 °
Color	grey
CRI	>80
Binning	5
LXXBXX data	70/50
Service life	30000 h

							4				4			4		4		4	ч	ч	ч	4	7	ч	4	ч	4								
	4	- 4		a.	ă,	J.	J.	J	4	J	4	J	J	J.	J.	a,	ä	J.	ä																
ı,	L	1 1	ı	J	1	J	J	J	J	ä	J	J	a,	J.	ä	J	J		a,			J		J.		1	J.	ı	J.	ı	J,	١,	L	J	J.
					ă.			а		а		a.	a.		a.	а	a.	J.	J.	a.	a.	a.	a.	ı	ı	ă.	a.	ы							



BIG WHITE Page	268
----------------	-----

Notes		