




## IMPERVA 150 CW

LED Outdoor wall and ceiling light, IP66, grey, 3000K

The functional wall and ceiling light has a diffuser which creates a pleasant light distribution. The luminaire was designed with powerful LEDs and is available in several lengths. The IP luminaire can be fitted with a warm white or cool white LEDs as required. Thanks to the built-in ballast, the luminaire is ready for direct connection to the 230V mains voltage supply.



## TECHNICAL DATA

Item no.:	1001316
Lamps included	0
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	1050 mA/V
Length	156.0 cm
Width	12.0 cm
Height	10.8 cm
Net weight	2.361 kg
Gross weight	2.991 kg
IP Code	IP 66
Safety class	I
Impact resistance class	IK08
Assembly	Surface
Assembly details	Ceiling, Wall
Number of through-wires	30
Wattage	55 W
Lumen	6600 lm
Colour temperature	3000 Kelvin
Beam angle	120 °
Color	grey
CRI	>80
Binning	4



LXXBXX data	70/50
Service life	50000 h
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
BIG WHITE Page	365

**Notes**

---

---

---

---

---