




IMPERVA 150 CW

LED Outdoor wall and ceiling light, IP66, grey, 4000K

The functional wall and ceiling light has a diffuser which creates a pleasant light distribution. The luminaire was designed with powerful LEDs and is available in several lengths. The IP luminaire can be fitted with a warm white or cool white LEDS as required. Thanks to the built-in ballast, the luminaire is ready for direct connection to the 230V mains voltage supply.



TECHNICAL DATA

Lamps included Primary nominal voltage 220-240V ~50/60Hz mA/V Secondary power / secondary voltage Length 156.0 cm Width 12.0 cm Height 10.8 cm Net weight 3.002 kg Gross weight IP Code IP 66 Safety class I Impact resistance class Assembly Assembly details Ceiling,Wall Number of through-wires 300
Secondary power / secondary voltage 1050 mA/V Length 156.0 cm Width 12.0 cm Height 10.8 cm Net weight 3.002 kg Gross weight 3.374 kg IP Code IP 66 Safety class I Impact resistance class IK08 Assembly Surface Assembly details Ceiling, Wall
Voltage 156.0 cm Width 12.0 cm Height 10.8 cm Net weight 3.002 kg Gross weight 3.374 kg IP Code IP 66 Safety class I Impact resistance class IK08 Assembly Surface Assembly details Ceiling,Wall
Width 12.0 cm Height 10.8 cm Net weight 3.002 kg Gross weight 3.374 kg IP Code IP 66 Safety class I Impact resistance class IK08 Assembly Surface Assembly details Ceiling, Wall
Height 10.8 cm Net weight 3.002 kg Gross weight 3.374 kg IP Code IP 66 Safety class I Impact resistance class IK08 Assembly Surface Assembly details Ceiling, Wall
Net weight 3.002 kg Gross weight 3.374 kg IP Code IP 66 Safety class I Impact resistance class IK08 Assembly Surface Assembly details Ceiling,Wall
Gross weight 3.374 kg IP Code IP 66 Safety class I Impact resistance class IK08 Assembly Surface Assembly details Ceiling, Wall
IP Code IP 66 Safety class I Impact resistance class IK08 Assembly Surface Assembly details Ceiling, Wall
Safety class Impact resistance class Assembly Assembly details Ceiling, Wall
Impact resistance class Assembly Surface Assembly details Ceiling,Wall
Assembly Surface Assembly details Ceiling, Wall
Assembly details Ceiling, Wall
Number of through-wires 30
Tumbor of through wiles
Wattage 55 W
Lumen 7100 lm
Colour temperature 4000 Kelvin
Beam angle 120 °
Color grey
CRI >80
Binning 4





LXXBXX data	70/50
Service life	50000 h
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
BIG WHITE Page	365

Notes			