




## TEC KALU CW

LED Indoor surface-mounted wall and ceiling light, quad, black, 24°, 3000K

This futuristic 240V wall and ceiling light TEC KALU has individually rotating and swivelling lamp heads, equipped with warm white and dimmable Premium LEDs. The built-in LED driver is located within the main structure. An optionally available suspension allows pendulum mode. TEC KALU is supplied ready for direct connection to the 230V mains voltage supply.



## TECHNICAL DATA

Item no.:	1001433
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	700 mA/V
Vertical tilting range	120 °
Horizontal rotation range	360 °
Length	29.5 cm
Width	24.5 cm
Height	15.3 cm
Net weight	2.694 kg
Gross weight	3.462 kg
IP Code	IP 20
Safety class	I
Assembly	Surface
Assembly details	Ceiling
Dimming technology	trailing edge
Wattage	60 W
Lumen	3800 lm
Colour temperature	3000 Kelvin
Beam angle	24 °
Color	black
CRI	>80
Binning	6

## Accessories

1001435	TEC KALU suspension set , black
1001436	TEC KALU suspension set , white

LXXBXX data	70/50
Service life	40000 h
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
BIG WHITE Page	317

## Notes

---



---



---



---



---