


## LED Outdoor BEAM

## silver-grey, 50W, 5700K, 100°, IP65

Powerful OUTDOOR BEAM spot for illuminating areas and spaces. With a tiltable installation bracket and protection class IP65, the spot is suitable for outdoor installation on the wall, ceiling or on the floor. The electrical connection of the spot, which is available in warm white and neutral white, is made directly by the built-in driver and the connection lead with mains plug to the 230V mains supply. A wall bracket is available as an option for simplified wall installation.



## **TECHNICAL DATA**

\_

| Item no.:                           | 1001637                |  |
|-------------------------------------|------------------------|--|
| Lamps included                      | 0                      |  |
| Primary nominal voltage             | 220-240V ~50/60Hz mA/V |  |
| Secondary power / secondary voltage | 640 mA/V               |  |
| Vertical tilting range              | 90 °                   |  |
| Length                              | 28.6 cm                |  |
| Width                               | 15.0 cm                |  |
| Height                              | 23.6 cm                |  |
| Net weight                          | 3.71 kg                |  |
| Gross weight                        | 4.066 kg               |  |
| IP Code                             | IP 65                  |  |
| afety class                         |                        |  |
| Impact resistance class             | IK04                   |  |
| Impact resistance                   | 0,5 Joule              |  |
| Assembly                            | Surface                |  |
| Assembly details                    | Ceiling,Ground,Wall    |  |
| Wattage                             | 54 W                   |  |
| Lumen                               | 5100 lm                |  |
| Colour temperature                  | 5700 Kelvin            |  |
| Beam angle                          | 100 °                  |  |
| Color                               | grey                   |  |
| CRI                                 | >80                    |  |
|                                     |                        |  |



|             |  | Binning                     | 5       |
|-------------|--|-----------------------------|---------|
| Accessories |  | LXXBXX data                 | 70/50   |
|             |  | Service life                | 30000 h |
| 234344      | WALL MOUNTING BRACKET , for OUT-<br>DOOR BEAM and MILOX, silver, 50 cm | Maximum ambient temperature | 40 °C   |
| 234354      | WALL MOUNTING BRACKET , for OUT-<br>DOOR BEAM and MILOX, silver, 80 cm |                             |         |

Notes