


## LED OUTDOOR BEAM

## warm white, 50W, 3000K, 100°, IP65

Powerful OUTDOOR BEAM spot for illuminating areas and spaces. With a tiltable installation bracket and protection class IP65, the spot is suitable for outdoor installation on the wall, ceiling or on the floor. The electrical connection of the spot, which is available in warm white and neutral white, is made directly by the built-in driver and the connection lead with mains plug to the 230V mains supply. A wall bracket is available as an option for simplified wall installation.



## **TECHNICAL DATA**

\_

Item no.:	1001638	
Lamps included	0	
Primary nominal voltage	220-240V ~50/60Hz mA/V	
Secondary power / secondary voltage	640 mA/V	
Vertical tilting range	90 °	
Length	28.6 cm	
Width	15.0 cm	
Height	23.6 cm	
Net weight	3.712 kg	
Gross weight	4.077 kg	
IP Code	IP 65	
Safety class	1	
Impact resistance class	IK04	
npact resistance 0,5 Joule		
Assembly	Surface	
Assembly details	embly details Ceiling,Ground,Wall	
Wattage	tage 54 W	
Lumen	5100 lm	
Colour temperature	3000 Kelvin	
Beam angle	m angle 100 °	
Color	grey	
CRI	>80	



		Binning	3
Accessories		LXXBXX data	70/50
		Service life	30000 h
234344	WALL MOUNTING BRACKET , for OUT- DOOR BEAM and MILOX, silver, 50 cm	Maximum ambient temperature	40 °C
234354	WALL MOUNTING BRACKET , for OUT- DOOR BEAM and MILOX, silver, 80 cm		

Notes