




LED FLOOD LIGHT

matt white, 30W, warm white, 100°

Powerful FLOOD LIGHT spot for illuminating areas and spaces. With a tiltable installation bracket and protection class IP65, the spot is suitable for outdoor installation on the wall, ceiling or on the floor. The electrical connection of the spot, which is available in warm white and neutral white, is made directly by the built-in driver and the connection lead with mains plug to the 230V mains supply. An earth spike is available as an option for simplified floor installation.



TECHNICAL DATA

Item no.:	1001643
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	760 mA/V
Vertical tilting range	180 °
Length	25.0 cm
Width	8.0 cm
Height	32.0 cm
Net weight	2.692 kg
Gross weight	2.984 kg
IP Code	IP 65
Safety class	I
Impact resistance class	IK04
Impact resistance	0,5 Joule
Assembly	Surface
Assembly details	Ceiling,Ground,Wall
Wattage	32 W
Lumen	2200 lm
Colour temperature	3000 Kelvin
Beam angle	90 °
Color	black
CRI	>80
Binning	3

Accessories

234340	Wall bracket , for Outdoor Beam and MI-LOX floodlight, black, 50cm
234350	WALL BRACKET , for SPOODI 15/20/31, black, 80 cm
900011	PLASTIC EARTH SPIKE , black, length 17.5cm

LXXBXX data	70/50
Service life	30000 h
Maximum ambient temperature	40 °C

Notes
