


LIPACL

LED Outdoor surface-mounted ceiling light, IP54, white, 3000/4000K

SLV LIPA robust, water-protected surface-mounted solution. Round wall and ceiling light made from aluminium. Thanks to its IP54 protection class it is suitable for outdoor use. The opal illuminated area has an LED light source beneath it which can be switched between warm and cool white, and is enclosed by the painted housing. The luminaire comes in several colour versions and is connected directly to the 230V mains supply thanks to its built-in LED driver.



TECHNICAL DATA

Item no.:	1001855		
Lamps included	0		
Primary nominal voltage	220-240V ~50/60Hz mA/V		
Secondary power / secondary voltage	500 mA/V		
Height	6.3 cm		
Diameter	28.0 cm		
Net weight	1.9 kg		
Gross weight	2.033 kg		
IP Code	IP 54		
Safety class	I		
Impact resistance class	IK05		
Impact resistance	0,6999999999999999999999999999999999999		
Assembly	Surface		
Assembly details	Ceiling, Wall		
Dimming technology	trailing edge		
Number of through-wires	10		
Wattage	24 W		
Lumen	1600 lm		
Colour temperature	3000/4000 Kelvin		
Color	white		
CRI	>80		
Binning	5		
	•		





LXXBXX data	70/50
Service life	30000 h
Maximum ambient temperature	35 °C
BIG WHITE Page	716

Notes			