

ENOLA ROUND L

outdoor LED surface-mounted ceiling light anthracite CCT 3000/4000K

The ENOLA SQUARE and ROUND series of puristic luminaires consist of a cylindrical or square aluminium construction, and are equipped with powerful LEDs. The light colour can be switched between 3000K and 4000K during installation using the built-in CCT. Because of the built-in LED driver, the electrical connection of the luminaire is made directly to a 230V mains voltage supply. In order to cover as wide a range of uses as possible, single and double headed wall lights and ceiling lights are available in round and square version in various sizes. This luminaire contains built-in LED lamps.



TECHNICAL DATA

Item no.:	1003442
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	900 mA/V
Height	22.3 cm
Diameter	14.0 cm
Net weight	1.6 kg
Gross weight	1.712 kg
IP Code	IP 65
Safety class	I
Impact resistance class	IK02
Impact resistance	0,20000000000000001 Joule
Assembly	Surface
Assembly details	Ceiling, Ceiling with Acc.
Number of through-wires	10
Number of through-wires Wattage	10 35 W
Wattage	35 W
Wattage Lumen	35 W 2500 / 2800 lm
Wattage Lumen Colour temperature	35 W 2500 / 2800 lm 3000/4000 Kelvin
Wattage Lumen Colour temperature Beam angle	35 W 2500 / 2800 Im 3000/4000 Kelvin 38 °
Wattage Lumen Colour temperature Beam angle Color	35 W 2500 / 2800 Im 3000/4000 Kelvin 38 ° anthracite
Wattage Lumen Colour temperature Beam angle Color CRI	35 W 2500 / 2800 Im 3000/4000 Kelvin 38 ° anthracite >90

							-				-			-		-		4	-	-	ч,	ч.	4	т.	ч.	4	-										
	- 4	- 4		ä	a,	J	J	J	J	a	J	J	J	J	J	ä	ä	a,	a,																		
ı	1 1	1 1	J	J	J	J	J	J	ä	4	ā	J	J	J	J	J	4		4			1		1		4	J.	ı	J.	4	a,	1	J.	ı	ı	١,	
										-		- 1	- 1	- 1	- 1					10		10				10											



Accessories

1003479	Spacer set , for the ENOLA SQUARE OUT and ROUND OUT ceiling lights in anthracite
---------	--

Service life	30000 h
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
BIG WHITE Page	705

Notes			