# NUMINOS® CL PHASE S

**Indoor LED recessed ceiling light white/black 4000K 36°**

No two projects are the same. But many projects demand a coherent lighting and design concept. NUMINOS® is a perfectly coordinated lighting system that harmonises function, design and technology. For planners and doers, for every requirement and for maximum variety with minimum effort. From hotels and offices to commercial or private rooms. From application to technology to design in detail: the modular downlights and spotlights can be configured exactly as required by the design or spatial conditions in question. The more multifaceted your project is, the more you can benefit from the intelligent NUMINOS® lighting family. Thanks to the wide selection of modules, there is a suitable solution for every need. The NUMINOS® lighting system, which can be configured and combined, offers over a thousand possibilities. Like this rigid ceiling-mounted spotlight, which is the perfect choice for creating even lighting from the ceiling and accent lighting for specific areas. With the best workmanship and light quality, which is infinitely variable thanks to the integrated LED driver (phase dimming). This means that easy installation is a mere formality. When will you choose SLV's modular variety? Here you can find the configurator: www.NU-MINOS.SLV.com

## TECHNICAL DATA

| | |
|---|---|
| Item no.: | 1004143 |
| Primary nominal voltage | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 250 mA/V |
| Height | 16.2 cm |
| Diameter | 6.5 cm |
| Net weight | 0.39 kg |
| Gross weight | 0.417 kg |
| Safety class | I |
| Assembly | Surface |
| Assembly details | Ceiling |
| Dimming technology | trailing edge |
| Wattage | 10.42 W |
| Lumen | 1100 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 36 ° |
| Color | white |
| CRI | >90 |
| UGR ≤ | 16 |
| Binning | 3 |
| LXXBXX data | 70/50 |
| Service life | 50000 h |
| BIG WHITE Page | 55 |

**Notes**