

NUMINOS® SPOT DALI S

Indoor LED recessed ceiling light white/black 2700K $\rm 60^{\circ}$

No two projects are the same. But many projects demand a coherent lighting and design concept. NUMINOS® is a perfectly coordinated lighting system that harmonises function, design and technology. For planners and doers, for every requirement and for maximum variety with minimum effort. From hotels and offices to commercial or private rooms. From application to technology to design in detail: the modular downlights and spotlights can be configured exactly as required by the design or spatial conditions in question. The more multifaceted your project is, the more you can benefit from the intelligent NUMINOS® lighting system. Thanks to the wide selection of modules, there is a suitable solution for every need. The $\ensuremath{\mathsf{NUMINOS}}\xspace{\mathbbmath{\mathbb{R}}}$ lighting family, which can be configured and combined, offers over a thousand possibilities. Like this pivoting ceiling-mounted spotlight, which is suitable for illuminating shelves and creating accent lighting for objects in living spaces, gastronomic establishments, or shops. With the best workmanship and light quality, which can be flexibly linked and centrally controlled thanks to the integrated LED driver (DALI dimming). This means that easy installation is a mere formality. When will you choose SLV's modular variety? Here you can find the configurator: www.NUMINOS.SLV.com

TECHNICAL DATA

Primary nominal voltage220-240V ~50/60Hz mA/VSecondary power / secondary voltage250 mA/VVertical tilting range90 °Horizontal rotation range350 °Length16.2 cmHeight14.5 cmDiameter6.5 cmNet weight0.621 kgSafety classIAssemblySurfaceAssembly detailsCeiling,WallDimming technologyDALIWattage10.42 W
Vertical tilting range90 °Horizontal rotation range350 °Length16.2 cmHeight14.5 cmDiameter6.5 cmNet weight0.58 kgGross weight0.621 kgSafety classIAssemblySurfaceAssembly detailsCeiling,WallDimming technologyDALI
Horizontal rotation range350 °Length16.2 cmHeight14.5 cmDiameter6.5 cmNet weight0.58 kgGross weight0.621 kgSafety classIAssemblySurfaceAssembly detailsCeiling,WallDimming technologyDALI
Length16.2 cmHeight14.5 cmDiameter6.5 cmNet weight0.58 kgGross weight0.621 kgSafety classIAssemblySurfaceAssembly detailsCeiling,WallDimming technologyDALI
Height14.5 cmDiameter6.5 cmNet weight0.58 kgGross weight0.621 kgSafety classIAssemblySurfaceAssembly detailsCeiling,WallDimming technologyDALI
Diameter6.5 cmNet weight0.58 kgGross weight0.621 kgSafety classIAssemblySurfaceAssembly detailsCeiling,WallDimming technologyDALI
Net weight 0.58 kg Gross weight 0.621 kg Safety class I Assembly Surface Assembly details Ceiling,Wall Dimming technology DALI
Gross weight 0.621 kg Safety class I Assembly Surface Assembly details Ceiling,Wall Dimming technology DALI
Safety class I Assembly Surface Assembly details Ceiling,Wall Dimming technology DALI
Assembly Surface Assembly details Ceiling,Wall Dimming technology DALI
Assembly details Ceiling,Wall Dimming technology DALI
Dimming technology DALI
Wattage 10.42 W
Lumen 980 lm
Colour temperature 2700 Kelvin
Beam angle 60 °
Color white
CRI >90
UGR ≤ 19
Binning 3



LXXBXX data	70/50
Service life	50000 h
BIG WHITE Page	49

Notes

Last updated 2021-01-22 13:26:41 | Subject to technical changes