

NUMINOS® SPOT DALI S

Indoor LED recessed ceiling light black/black 4000K 36°

No two projects are the same. But many projects demand a coherent lighting and design concept. NUMINOS® is a perfectly coordinated lighting system that harmonises function, design and technology. For planners and doers, for every requirement and for maximum variety with minimum effort. From hotels and offices to commercial or private rooms. From application to technology to design in detail: the modular downlights and spotlights can be configured exactly as required by the design or spatial conditions in question. The more multifaceted your project is, the more you can benefit from the intelligent NUMINOS® lighting system. Thanks to the wide selection of modules, there is a suitable solution for every need. The NUMINOS® lighting family, which can be configured and combined, offers over a thousand possibilities. Like this pivoting ceiling-mounted spotlight, which is suitable for illuminating shelves and creating accent lighting for objects in living spaces, gastronomic establishments, or shops. With the best workmanship and light quality, which can be flexibly linked and centrally controlled thanks to the integrated LED driver (DALI dimming). This means that easy installation is a mere formality. When will you choose SLV's modular variety? Here you can find the configurator: www.NUMINOS.SLV.com

TECHNICAL DATA

Primary nominal voltage220-240V ~50/60Hz mAVVSecondary power / secondary voltage250 mAVVVertical tilting range90 °Horizontal rotation range350 °Length16.2 cmHeight14.5 cmDiameter6.5 cmNet weight0.58 kgGross weight0.621 kgSafety classIAssemblySurfaceAssembly detailsCeiling,WallDimming technologyDALIWattage10.42 WLumen1100 lmColour temperature4000 KelvinBeam angle36 °Colorblack	Item no.:	1004403
Vertical tilting range90 °Horizontal rotation range350 °Length16.2 cmHeight14.5 cmDiameter6.5 cmNet weight0.621 kgGross weight0.621 kgSafety classIAssemblyCeiling,WallDimming technologyDALIWattage10.42 WLumen1100 ImColour temperature4000 KelvinBeam angle36 °	Primary nominal voltage	220-240V ~50/60Hz mA/V
Horizontal rotation range350 °Length16.2 cmHeight14.5 cmDiameter6.5 cmNet weight0.58 kgGross weight0.621 kgSafety classIAssemblySurfaceAssembly detailsCeiling,WallDimming technologyDALIWattage10.42 WLumen1100 lmColour temperature4000 KelvinBeam angle36 °	Secondary power / secondary voltage	250 mA/V
Length16.2 cmHeight14.5 cmDiameter6.5 cmNet weight0.58 kgGross weight0.621 kgSafety classIAssemblySurfaceAssembly detailsCeiling,WallDimming technologyDALIWattage10.42 WLumen1100 lmColour temperature4000 KelvinBeam angle36 °	Vertical tilting range	90 °
Height14.5 cmDiameter6.5 cmNet weight0.58 kgGross weight0.621 kgSafety classIAssemblySurfaceAssembly detailsCeiling,WallDimming technologyDALIWattage10.42 WLumen1100 lmColour temperature4000 KelvinBeam angle36 °	Horizontal rotation range	350 °
Diameter6.5 cmNet weight0.58 kgGross weight0.621 kgSafety classIAssemblySurfaceAssembly detailsCeiling,WallDimming technologyDALIWattage10.42 WLumen1100 lmColour temperature4000 KelvinBeam angle36 °	Length	16.2 cm
Net weight0.58 kgGross weight0.621 kgSafety classIAssemblySurfaceAssembly detailsCeiling,WallDimming technologyDALIWattage10.42 WLumen1100 lmColour temperature4000 KelvinBeam angle36 °	Height	14.5 cm
Gross weight0.621 kgSafety classIAssemblySurfaceAssembly detailsCeiling,WallDimming technologyDALIWattage10.42 WLumen1100 lmColour temperature4000 KelvinBeam angle36 °	Diameter	6.5 cm
Safety classIAssemblySurfaceAssembly detailsCeiling,WallDimming technologyDALIWattage10.42 WLumen1100 ImColour temperature4000 KelvinBeam angle36 °	Net weight	0.58 kg
AssemblySurfaceAssembly detailsCeiling,WallDimming technologyDALIWattage10.42 WLumen1100 lmColour temperature4000 KelvinBeam angle36 °	Gross weight	0.621 kg
Assembly details Ceiling,Wall Dimming technology DALI Wattage 10.42 W Lumen 1100 lm Colour temperature 4000 Kelvin Beam angle 36 °	Safety class	1
Dimming technologyDALIWattage10.42 WLumen1100 lmColour temperature4000 KelvinBeam angle36 °	Assembly	Surface
Wattage 10.42 W Lumen 1100 lm Colour temperature 4000 Kelvin Beam angle 36 °	Assembly details	Ceiling,Wall
Lumen 1100 lm Colour temperature 4000 Kelvin Beam angle 36 °	Dimming technology	DALI
Colour temperature 4000 Kelvin Beam angle 36 °	Wattage	10.42 W
Beam angle 36 °	Lumen	1100 lm
	Colour temperature	4000 Kelvin
Color black	Beam angle	36 °
	Color	black
CRI >90	CRI	>90
UGR ≤ 16	UGR≤	16
Binning 3	Binning	3



LXXBXX data	70/50
Service life	50000 h
BIG WHITE Page	49

Notes

Last updated 2021-01-22 13:26:41 | Subject to technical changes