




MARONA

ceiling light, LED, 3000K, round, brushed aluminium, 4x3W

The MARONA ceiling light impresses with its elegant shape and clear contrast between the materials used - steel and acrylic glass. A dimmable 4x3W LED module provides the desired lighting effect and makes the luminaire ready for direct connection to the 230V mains supply. The deliberately selected generous distance between the lamp shade and the mounting surface creates a corona effect with indirect illumination properties.



TECHNICAL DATA

Item no.:	155156
Primary nominal voltage	200-240V ~50/60Hz mA/V
Secondary power / secondary voltage	430 mA/V
Height	8.6 cm
Diameter	30.0 cm
Net weight	0.669 kg
Gross weight	1.055 kg
IP Code	IP 20
Safety class	I
Assembly	Surface
Assembly details	Ceiling, Wall
Dimming technology	Leading edge,trailing edge
Dimming technology Wattage	Leading edge,trailing edge 15 W
Wattage	15 W
Wattage Lumen	15 W 1200 lm
Wattage Lumen Colour temperature	15 W 1200 lm 3000 Kelvin
Wattage Lumen Colour temperature Beam angle	15 W 1200 Im 3000 Kelvin 120 °
Wattage Lumen Colour temperature Beam angle Color	15 W 1200 Im 3000 Kelvin 120 ° grey
Wattage Lumen Colour temperature Beam angle Color CRI	15 W 1200 Im 3000 Kelvin 120 ° grey >80
Wattage Lumen Colour temperature Beam angle Color CRI Binning	15 W 1200 Im 3000 Kelvin 120 ° grey >80 6
Wattage Lumen Colour temperature Beam angle Color CRI Binning LXXBXX data	15 W 1200 Im 3000 Kelvin 120 ° grey >80 6 70/50

							ч				4			ч		4		ч	ч	ч	ч	4	7	ч	ч	ч	4									
	- 4	- 4		a,	a,	J.	J.	J	J	J	J	J	J	J	ä	ä	ä	ä	J.																	
ı	LL	1 1	ı	J	J	J	J	J.	J	ä	J	J	J	J	J	J	J		4			ı		1		1	4	1	ı	ı	a,	J.	ı	ı	1	١,
					ä			á		ä		J	ä	J	ä	J	J	J	J.	J	ă,	a.	J.	J	J	J	J.	ă,								



Notes				