



## **RASTO**

ceiling light, LED, 3000K, white, L/W/H 124.5/17.5/4 cm, 4100lm, can be converted to a pendant, 36 W  $\,$ 

The elongated RASTO LED surface-mounted ceiling light with a white painted light body impresses with its clear design and effective lighting properties. The luminaire is fitted with a high-gloss reflector which thus provides a downward radiating, glare-free light for use in offices, corridors, conference rooms and much more. Thanks to the pre-installed LED driver, the RASTO LED surface-mounted ceiling light is ready for direct connection to the 230V mains supply. A suspension set is available as an accessory. This luminaire contains six built-in 9.3W LED lamps.





## **TECHNICAL DATA**

| Item no.:                           | 158961                 |  |
|-------------------------------------|------------------------|--|
| Lamps included                      | 0                      |  |
| Number of different light outlets   | 1                      |  |
| Primary nominal voltage             | 230-240V ~50/60Hz mA/V |  |
| Secondary power / secondary voltage | 700 mA/V               |  |
| Length                              | 124.5 cm               |  |
| Width                               | 17.5 cm                |  |
| Height                              | 4.0 cm                 |  |
| Net weight                          | 2.977 kg               |  |
| Gross weight                        | 4.641 kg               |  |
| IP Code                             | IP 20                  |  |
| Safety class                        | I                      |  |
| Assembly                            | Surface                |  |
| Assembly details                    | Ceiling with Acc.      |  |
| Wattage                             | 36 W                   |  |
| Lumen                               | 4100 lm                |  |
| Colour temperature                  | 3000 Kelvin            |  |
| Beam angle                          | 85 °                   |  |
| Color                               | white                  |  |
| CRI                                 | >80                    |  |
| UGR≤                                | 19                     |  |
| LXXBXX data                         | 70/50                  |  |
| ·                                   |                        |  |





| Service life | 50000 h |
|--------------|---------|
|--------------|---------|

| Notes |  |  |
|-------|--|--|
|       |  |  |
|       |  |  |
|       |  |  |
|       |  |  |
|       |  |  |
|       |  |  |
|       |  |  |
|       |  |  |
|       |  |  |