




TERANG 2

outdoor wall and ceiling light, LED, 3000K, IP44, oval, anthracite, 11W

A new interpretation of the classical construction luminaires for wall and ceiling mounting with a pre-installed powerful LED module. Available with housing colours of white, silver-grey, anthracite and rust, the TERANG 2 XL has frosted round glass, which guarantees homogeneous distribution of its light. With protection class IP44, this luminaire is also designed for use outdoors. Thanks to its pre-installed LED driver, the TERANG 2 is ready for direct connection to a 230V mains supply.



TECHNICAL DATA

Lamps included0Primary nominal voltage220-240V ~50Hz mA/VWidth19.8 cmHeight11.0 cmDepth7.5 cmNet weight0.466 kgGross weight0.56 kgIP CodeIP 44Safety classIImpact resistance classIK03AssemblySurface
Width 19.8 cm Height 11.0 cm Depth 7.5 cm Net weight 0.466 kg Gross weight 0.56 kg IP Code IP 44 Safety class I Impact resistance class IK03 Assembly Surface
Height
Depth 7.5 cm Net weight 0.466 kg Gross weight 0.56 kg IP Code IP 44 Safety class I Impact resistance class IK03 Assembly Surface
Net weight 0.466 kg Gross weight 0.56 kg IP Code IP 44 Safety class I Impact resistance class IK03 Assembly Surface
Gross weight 0.56 kg IP Code IP 44 Safety class I Impact resistance class IK03 Assembly Surface
IP Code IP 44 Safety class I Impact resistance class IK03 Assembly Surface
Safety class Impact resistance class Assembly Surface
Impact resistance class IK03 Assembly Surface
Assembly Surface
Assembly details Ceiling, Wall
Wattage 11 W
Lumen 680 lm
Colour temperature 3000 Kelvin
Beam angle 120 °
Color anthracite
CRI >80
Binning 6
LXXBXX data 70/50
Service life 20000 h

							4				4			4		4		4	4	4	4	ч	4	4	4	4	4									
	- 4	- 4		J	J.	J	J	J	J.	a,	J	J	J	J	J,	a,	a,	a,	J,																	
ı,	L	l l	J	J	1	J	J	J.	4	ä	J	J	a,	J	ä	J	ä		4			J		J.		ı	J	ı	J.	J	J.	١,	١,	1	ı	ı
					4					4		1	1	-1	1	1	а.	1	1	1	1	1	1	1	1	т.	4	т								



BIG WHITE Page	717
----------------	-----

Notes			