



FLAC BEAM

outdoor façade light, LED, 3000K, IP65, stone-grey, with Philips DLMi module 2000lm, 18W

The FLAC BEAM outdoor floodlights are fitted with high-performance LED modules made by Philips. The floodlight is made of aluminium and, thanks to the fitted mounting bracket, is suitable for installation on the wall, ceiling and floor. The electrical connection of the swivelling and tilting floodlight is made using the built-in two metre connection lead which includes an IP protected contact plug directly to the 230V mains supply. The floodlight has IP65 protection class and with approx. 1250 or approx. 1800lm, it is suitable for outdoor use. In addition, a HIT version for discharge lamps is available. This luminaire contains built-in LED lamps.





TECHNICAL DATA

| Item no.: | 231092 | | | |
|---------------------------|------------------------|--|--|--|
| Lamps included | 0 | | | |
| Primary nominal voltage | 220-240V ~50/60Hz mA/V | | | |
| Vertical tilting range | 170° | | | |
| Horizontal rotation range | 120 ° | | | |
| Height | 22.0 cm | | | |
| Diameter | 17.0 cm | | | |
| Net weight | 2.799 kg | | | |
| Gross weight | 3.198 kg | | | |
| IP Code | IP 65 | | | |
| Safety class | I | | | |
| Impact resistance class | IK04 | | | |
| Impact resistance | 0,5 Joule | | | |
| Assembly | Surface | | | |
| Assembly details | Ceiling, Ground, Wall | | | |
| Wattage | 18 W | | | |
| Lumen | 1250 lm | | | |
| Colour temperature | 3000 Kelvin | | | |
| Beam angle | 60 ° | | | |
| Color | grey | | | |
| CRI | >80 | | | |
| Binning | 3 | | | |
| | | | | |





| LXXBXX data | 70/50 |
|--------------|---------|
| Service life | 25000 h |

| Notes | | | |
|-------|--|--|--|
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |