





## DISOS

outdoor floodlight, LED, 4000K, black, 100W

Powerful DISOS LED floodlight to light up areas and courtyards. With a tiltable installation bracket and protection class Ip65, the floodlight is suitable for outdoor installation on the wall or on the floor. The electrical connection of the floodlight, which comes in cold-white, is done using the built-in driver and connection lead directly to the 230V mains supply. Various wall brackets are available for easy wall mounting. This luminaire contains built-in 90W LED lamps.



## TECHNICAL DATA

|                                     |                        |
|-------------------------------------|------------------------|
| Item no.:                           | 232380                 |
| Lamps included                      | 0                      |
| Number of different light outlets   | 1                      |
| Primary nominal voltage             | 100-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 48 mA/V                |
| Length                              | 26.0 cm                |
| Width                               | 15.0 cm                |
| Height                              | 31.0 cm                |
| Net weight                          | 5.355 kg               |
| Gross weight                        | 6.723 kg               |
| IP Code                             | IP 65                  |
| Safety class                        | I                      |
| Impact resistance class             | IK06                   |
| Impact resistance                   | 1 Joule                |
| Assembly                            | Surface                |
| Assembly details                    | Ground,Wall            |
| Wattage                             | 100 W                  |
| Lumen                               | 10600 lm               |
| Colour temperature                  | 4000 Kelvin            |
| Beam angle                          | 110 °                  |
| Color                               | black                  |
| CRI                                 | >80                    |



|              |         |
|--------------|---------|
| Binning      | 6       |
| LXXBXX data  | 70/50   |
| Service life | 35000 h |

### Accessories

|        |                              |
|--------|------------------------------|
| 228730 | CONNECTION BOX , 3-pin, IP68 |
|--------|------------------------------|

### Notes

---

---

---

---

---