



ENOLA_C

outdoor display fitting, LED, 3000K, IP55, round, white

The display fitting of the ENOLA_C series is made from a painted aluminium and glass cylinder covering the incorporated COB LED. The lamp head mounted on the curved extension rod is rotatable and tiltable. With protection class IP55, it is suitable for outdoor use. The electrical connection of the luminaire, which comes in various colours, is directly to the 230V mains supply. The ENOLA_C series includes other wall and ceiling lights and can therefore be used universally.





TECHNICAL DATA

Item no.:	228531
Lamps included	0
Primary nominal voltage	100-240V ~50/60Hz mA/V
Secondary power / secondary voltage	500 mA/V
Length	72.0 cm
Height	11.7 cm
Depth	10.0 cm
Net weight	1.213 kg
Gross weight	1.826 kg
IP Code	IP 55
Safety class	I
Assembly	Surface
Assembly details	Wall
Wattage	12 W
Lumen	900 lm
Colour temperature	3000 Kelvin
Beam angle	55 °
Color	white
CRI	>80
LXXBXX data	70/50
Service life	40000 h

							ч				4			ч		4		ч	ч	ч	ч	4	7	ч	ч	ч	4									
	- 4	- 4		a,	a,	J.	J.	J	J	J	J	J	J	J	ä	ä	ä	ä	J.																	
ı	LL	1 1	ı	J	J	J	J	J.	J	ä	J	J	J	J	J	J	J		4			ı		1		1	4	1	ı	ı	a,	J.	ı	ı	1	١,
					ä			á		ä		J	ä	J	ä	J	J	J	J.	J	ă,	a.	J.	J	J	J	J.	ă,								



Notes				