



KALU FLOOR 2 floor stand

double-headed, QR-LP111, round, brushed aluminium, max. 100 W

The puristic basic design of the KALU FLOOR 2 floor stand is a guarantor for absolutely individual alignment of the lamp heads, which are equipped with halogen QRB. Equipped with soft-start function, the incorporated electronic transformer protects the bulbs from potential damage from over-voltage. Available in brushed aluminium colour, KALU FLOOR 2 floor stand is supplied ready for direct connection to 230V mains supply.

TECHNICAL DATA

Item no.:	147296
Socket	G53
Lamp	QR111
Number of sockets	2
Lamps included	0
Primary nominal voltage	230V ~50Hz mA/V
Secondary power / secondary voltage	12 mA/V
Tilt range	90 °
Horizontal rotation range	350 °
Length	30.0 cm
Width	9.0 cm
Height	19.2 cm
Net weight	1.064 kg
Gross weight	1.342 kg
IP Code	IP 20
Safety class	II
Impact resistance class	IK03
Impact resistance	0,3499999999999998 Joule
Assembly	Mobile
Wattage	50 W
Color	aluminium



Recommended lamp

560231	PHILIPS MASTER LED AR111 , CRI90, 15W, 24°, 2700K, dimmable
560233	PHILIPS MASTER LED AR111 , CRI90, 15W, 24°, 3000K, dimmable

Notes
