



## KALU FLOOR 1 floor stand

single-headed, QR-LP111, round, brushed aluminium, max. 50  $\ensuremath{\mathrm{W}}$ 

The puristic design of KALU FLOOR 1 is a guarantor for absolutely individual alignment of lamp heads, optionally equipped with QRB halogen or suitable LED lamps. Equipped with soft-start function, the incorporated electronic transformer protects the bulbs from potential damage from over-voltage. Available in brushed aluminium colour, KALU FLOOR 1 floor stand is supplied ready for direct connection to 230V mains supply.

## **TECHNICAL DATA**

Item no.:	147286		
Socket	G53		
Lamp	QR111		
Number of sockets	1		
Lamps included	0		
Primary nominal voltage	230V ~50Hz mA/V		
Secondary power / secondary voltage	12 mA/V		
Tiltrange	90 °		
Horizontal rotation range	350 °		
Length	15.0 cm		
Width	9.0 cm		
Height	19.2 cm		
Net weight	0.736 kg		
Gross weight	0.911 kg		
IP Code	IP 20		
Safety class	I		
Impact resistance class	IK03		
Impact resistance	0,34999999999999999999999999999999999999		
Assembly	Mobile		
Wattage	50 W		
Color	aluminium		





## Recommended lamp

560231	PHILIPS MASTER LED AR111 , CRI90, 15W, 24°, 2700K, dimmable
560233	PHILIPS MASTER LED AR111 , CRI90, 15W, 24°, 3000K, dimmable

Notes			