




PATHLIGHT 40

LED outdoor floor stand, rust coloured, IP55, 3000K

The direct radiating floor stands of the RUSTY series convince by their exceptional rust look. This is achieved by a special chemical treatment of the FeCSi steel used. This makes the luminaire a unique piece and an absolutely special feature wherever they are installed. With protection class IP55, it is suitable for outdoor use. As an option an earth spike as well as a connection box for safe electrical connection to the round luminaire upright, are available. Equipped with a powerful LED, the luminaire connects directly to a 230V mains voltage supply.



TECHNICAL DATA

Item no.:	1001823
Number of different light outlets	1
Primary nominal voltage	220-240V ~50/60Hz mA/V
Length	15.0 cm
Width	25.0 cm
Height	40.0 cm
Net weight	12.705 kg
Gross weight	13.966 kg
IP Code	IP 55
Safety class	I
Impact resistance class	IK06
Impact resistance	1 Joule
Assembly	Surface
Assembly details	Ground
Wattage	8.9 W
Lumen	400 lm
Colour temperature	3000 Kelvin
Beam angle	90 °
Color	rust
CRI	>80
Binning	3
LXXBXX data	70/50

Accessories

228730	CONNECTION BOX , 3-pin, IP68
229422	Earth spike , galvanised steel, 50 cm

Service life	25000 h
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
BIG WHITE Page	603

Notes
