





BENDO

outdoor pathway and floor stand, LED, 3000K, anthracite, L/W/H 32/21/42 cm

The angled aluminium BENDO floor stand is fitted with a large number of powerful LEDs. With protection class IP55, it is suitable for outdoor use. Available in three sizes, it is supplied with open cable ends for simple installation. A concrete anchor, connection box and T-connection box are available as an option. This floor stand from the Carsten Witsch designed series of luminaires, contains built-in LED lamps. The LED cannot be changed in the luminaire.



TECHNICAL DATA

Item no.:	231825
Lamps included	0
Number of different light outlets	1
Primary nominal voltage	220-240V ~50/60Hz mA/V
Length	32.0 cm
Width	21.0 cm
Height	42.0 cm
Net weight	2.334 kg
Gross weight	3.559 kg
IP Code	IP 55
Safety class	I
Impact resistance class	IK06
Impact resistance	1 Joule
Assembly	Surface
Assembly details	Ground, Ground with Acc.
Dimming technology	Leading edge
Wattage	6.5 W
Lumen	420 lm
Colour temperature	3000 Kelvin
Beam angle	80 °
Color	anthracite
CRI	>80

Accessories

228726	T-CONNECTIONBOX , black, IP68
228730	CONNECTION BOX , 3-pin, IP68
231849	CONCRETE ANCHOR , for BENDO outdoor floor stand, silver

Binning	6
LXXBXX data	70/50
Service life	35000 h
Minimum ambient temperature	-25 °C
Maximum ambient temperature	50 °C

Notes
