





## BENDO

outdoor floor stand, LED, 3000K, IP55, anthracite, L/W/H 35/21/80 cm, 12W

The angled aluminium BENDO floor stand is fitted with a large number of powerful LEDs. With protection class IP55, it is suitable for outdoor use. Available in three sizes, it is supplied with open cable ends for simple installation. A concrete anchor, connection box and T-connection box are available as an option. This luminaire contains built-in LED lamps. The LED cannot be changed in the luminaire.



## TECHNICAL DATA

Item no.:	231835
Lamps included	0
Number of different light outlets	1
Primary nominal voltage	220-240V ~50/60Hz mA/V
Length	35.0 cm
Width	21.0 cm
Height	80.0 cm
Net weight	3.261 kg
Gross weight	5.238 kg
IP Code	IP 55
Safety class	I
Impact resistance class	IK06
Impact resistance	1 Joule
Assembly	Surface
Assembly details	Ground, Ground with Acc.
Dimming technology	Leading edge
Wattage	11 W
Lumen	700 lm
Colour temperature	3000 Kelvin
Beam angle	80 °
Color	anthracite
CRI	>80

## Accessories

228726	T-CONNECTIONBOX , black, IP68
228730	CONNECTION BOX , 3-pin, IP68
231849	CONCRETE ANCHOR , for BENDO outdoor floor stand, silver

Binning	6
LXXBXX data	70/50
Service life	35000 h
Minimum ambient temperature	-25 °C
Maximum ambient temperature	50 °C
BIG WHITE Page	602

## Notes

---



---



---



---



---