





H-POL

pathway and floor stand, single-headed, LED, 3000K, anthracite, L/W/H 16.5/16.5/66 cm

The H-POL SINGEL indirect radiating floor stand is made of aluminium and plastic. With protection class IP55, it is suitable for outdoor use. Thanks to the 8W LED, the luminaire is ideal for use as a pathway light. The product is designed for floor installation and is through-wireable. A large mounting pot is available for optimum mounting in the earth. Thanks to the built-in LED driver, it can be connected directly to the 230V mains supply.



TECHNICAL DATA

| | |
|-------------------------------------|--------------------------|
| Item no.: | 232165 |
| Lamps included | 0 |
| Number of different light outlets | 1 |
| Primary nominal voltage | 100-277V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 500 mA/V |
| Length | 16.5 cm |
| Width | 16.5 cm |
| Height | 66.0 cm |
| Installation length | 11.8 cm |
| Installation width | 11.8 cm |
| Installation depth | 10.0 cm |
| Net weight | 2.358 kg |
| Gross weight | 3.154 kg |
| IP Code | IP 55 |
| Safety class | I |
| Assembly | Recessed |
| Assembly details | Ground, Ground with Acc. |
| Number of through-wires | 18 |
| Wattage | 18 W |
| Lumen | 700 lm |
| Colour temperature | 3000 Kelvin |
| Color | anthracite |



Accessories

| | |
|--------|--|
| 232195 | MOUNTING POT , for H-POL pathway and floor stand, anthracite |
|--------|--|

| | |
|----------------|---------|
| CRI | >80 |
| Binning | 6 |
| LXXBXX data | 70/50 |
| Service life | 30000 h |
| BIG WHITE Page | 596 |

Notes
