

DASAR PROJECTOR

outdoor floodlight, LED, 3000K, IP67, anodised aluminium, 230V, 6W

The surface-mounted DASAR PROJECTOR series lights are fitted with a 6W premium LED and available with a warm-white colour of light. The electrical connection is to a compatible 12V or 24V DC power supply. With IP68 protection class, the luminaire is suitable for outdoor use. The anodised aluminium DASAR PROJECTOR series includes a further stainless steel version, among other things. This luminaire has built-in LED lamps and can be used as a spike luminaire with an earth spike. The lamps in the luminaire cannot be replaced.

TECHNICAL DATA

Item no.:	233561	
Primary nominal voltage	220-240V ~50/60Hz mA/V	
Secondary power / secondary voltage	400 mA/V	
Vertical tilting range	90 °	
Length	7.2 cm	
Width	10.0 cm	
Height	10.8 cm	
Net weight	0.739 kg	
Gross weight	0.81 kg	
IP Code	IP 67	
Safety class	1	
Impact resistance class	IK04	
Impact resistance	0,5 Joule	
Assembly	Surface	
Assembly details	Ceiling, Ceiling with Acc., Ground, Ground with Acc., Wall, Wall with Acc.	
Wattage	5.5 W	
Lumen	300 lm	
Colour temperature	3000 Kelvin	
Beam angle	40 °	
Color	aluminium	
CRI	>80	
Binning	6	
	1	





Accessories

233580	EARTH SPIKE , for DASAR PROJECTOR, stainless steel 316
233582	INSTALLATION PLATE , for DASAR PRO- JECTOR outdoor floodlight, stainless steel 316
900011	PLASTIC EARTH SPIKE , black, length 17.5cm

LXXBXX data	70/50
Service life	25000 h

Notes		