


## DASAR PROJECTOR

## outdoor floodlight, LED, 3000K, IP68, stainless steel 316, 12-24V, 7W

The surface-mounted DASAR PROJECTOR series lights are fitted with a 7W premium LED and available with a warm-white colour of light. The electrical connection is to a compatible 12V or 24V DC power supply. With IP68 protection class, the luminaire is suitable for outdoor use. The stainless steel DASAR PROJECTOR series includes a further aluminium version, among other things. This luminaire has built-in LED lamps and can be used as a spike luminaire with an earth spike. The lamps in the luminaire cannot be replaced.



## TECHNICAL DATA

| Item no.:               | 233570   |
|-------------------------|--|
| Primary nominal voltage | 12-24V mA/V  |
| Vertical tilting range  | 90 °   |
| Length                  | 7.2 cm   |
| Width                   | 10.0 cm  |
| Height                  | 10.8 cm  |
| Net weight              | 1.161 kg   |
| Gross weight            | 1.244 kg   |
| IP Code                 | IP 68  |
| Safety class            | 111  |
| Assembly                | Surface  |
| Assembly details        | Ceiling, Ceiling with Acc., Ground, Ground with Acc., Wall, Wall with Acc. |
| Wattage                 | 7 W  |
| Lumen                   | 360 lm   |
| Colour temperature      | 3000 Kelvin  |
| Beam angle              | 40 °   |
| Color                   | stainless steel  |
| CRI                     | >80  |
| Binning                 | 6  |
| LXXBXX data             | 70/50  |
| Service life            | 25000 h  |
| BIG WHITE Page          | 630  |
|                         |  |



## Accessories

| 233580 | EARTH SPIKE , for DASAR PROJECTOR, stainless steel 316                                   |
|--------|--|
| 233582 | INSTALLATION PLATE , for DASAR PRO-<br>JECTOR outdoor floodlight, stainless steel<br>316 |
| 470502 | LED POWER SUPPLY , 12W, 24V  |
| 470507 | LED POWER SUPPLY , 12W, 12V  |
| 900011 | PLASTIC EARTH SPIKE , black, length 17.5cm   |

Notes