



KELVIN CONTROL STRIP

LED, 2700-6500K, L/W 300/1 cm, 36 W, max. 3900lm

Flexible TUNABLE WHITE LED strip with max. 12 Watt per metre to connect to a 24V DC power supply. The rear side is fitted with adhesive tape to make for simple installation. Controlled by the KELVIN CONTROL System, the colour of light can be adjusted from 2700K to 6500K with constant brightness. The strip comes in various lengths.

TECHNICAL DATA

Item no.:	552863
Nominal voltage	24V DC V
Length	300.0 cm
Width	1.0 cm
Height	0.2 cm
Net weight	0.059 kg
Gross weight	0.109 kg
IP Code	IP 20
Safety class	III
Assembly	Surface
Assembly details	Ceiling, Ground, Wall
Lumen	1881 lm
Beam angle	120 °
Color	white
CRI	>80
Binning	3
Service life	25000 h
Switching cycles	12500

							ч				4			ч		4		ч	ч	ч	ч	4	7	ч	ч	ч	4									
	- 4	- 4		a,	a,	J.	J.	J	J	J	J	J	J	J	ä	ä	ä	ä	J.																	
ı	LL	1 1	ı	J	J	J	J	J.	J	ä	J	J	J	J	J	J	J		4			ı		4		1	4	1	ı	ı	a,	J.	ı	ı	1	١,
					ä			á		ä		J	ä	J	ä	J	J	J	J.	J	ă,	a.	J.	J	J	J	J.	ă,								



Notes				