



FLEXLED ROLL PRO

24V, 12W, 3000K, 1 m, 60 LED/m

High-performance flexible 24V DC LED strip of the PRO series . For simplified mounting the backside is covered with adhesive tape. The power input is given by a 24V PSU. This strip is available in several lengths and colours. Further available are connection leads, direct connectors and 90° soldering edges.

TECHNICAL DATA

Item no.:	552132
Nominal voltage	24V DC V
Length	100.0 cm
Width	1.0 cm
Height	0.2 cm
Net weight	0.025 kg
Gross weight	0.074 kg
IP Code	IP 20
Safety class	III
Wattage	12 W
Lumen	1020 lm
Colour temperature	3000 Kelvin
Beam angle	120 °
Color	white
CRI	>80
Binning	6
LED distance	1,7 cm
Service life	20000 h
Switching cycles	10000

							4				4			4		-		4	4	4	4	ч	4	4	4	4	4									
	J,	_1		4	4	J	4	4	4	4	4	ı	ı	J	4	4	4	4	a,																	
u	J	7 7	1	1	J	J	1	4	J	4	4	J	J	4	4	J	J		4			4		4		4	J.	J	J.	ı	a,	ı	ı	ı	ı	1
					a			а		а		a.	a.	ы	а	a.	a.	J.	J.	a.	a.	a.	J.	ı	ı	a.	а	a.								



Accessories

470502	LED POWER SUPPLY , 12W, 24V
--------	-----------------------------

Notes		