



FLEXLED ROLL RGB

24V, 41W, 5m, 48 LED/m

Flexible 24V DC LED RGB strip. For simplified mounting the backside is covered with adhesive tape. The power input is given by a 24V direct current power supply unit. We further offer accessory like feed cables and direct connectors. To control the various RGB effects a separately available controller is required.

TECHNICAL DATA

Item no.:	552123
Nominal voltage	24V DC V
Length	500.0 cm
Width	1.5 cm
Height	0.2 cm
Net weight	0.078 kg
Gross weight	0.206 kg
IP Code	IP 20
Safety class	III
Wattage	41 W
Beam angle	120 °
Color	copper
LED distance	2,1 cm
Service life	20000 h
Switching cycles	10000

Accessories

470506	LED POWER SUPPLY , 60W, 24V
470650	EASY LIM RF-MINI-RGB MASTER CONTROLLER , 12V/DC and 24V/DC, with remote controller
470651	EASY LIM RF-MINI-RGB-SLAVE , 12V/DC and 24V/DC
550418	FEED-IN , for FLEXLED ROLL RGB 24V up to 15mm wide, max. 50W, 50cm
550419	DIRECT CONNECTOR , for FLEXLED ROLL RGB 24V up to 15mm wide, max. 50W

Notes
