

FLEXLED ROLL

24V, 14W, 5700K, 3 m, 60 LED/m

Flexible 24V DC LED strip for outdoor usage. For simplified mounting the backside is covered with adhesive tape. The power input is given by a 24V direct current power supply unit. We further offer accessory like feed cables, direct connectors and 90° soldering edges.

TECHNICAL DATA

Item no.:	552111
Nominal voltage	24V DC V
Length	300.0 cm
Width	1.0 cm
Height	0.3 cm
Net weight	0.033 kg
Gross weight	0.138 kg
IP Code	IP 20
Safety class	III
Wattage	14 W
Lumen	1110 lm
Colour temperature	4000 Kelvin
Beam angle	120 °
CRI	>80
Binning	6
LED distance	1,7 cm
Service life	20000 h
Switching cycles	10000

							4				4			4		4		4	4	4	ч.	4	4	4	4	4	4									
	4	- 4		1	1	ı	J.	J	J	a,	J	J	J	J	J.	ä	ä	ä	ä																	
١,	1.1	1 1	. د	ı,	1	1	ı	J	J	a.	ä	J	4	J	J	J	4		a.			1		4		1	J.	ı	J.	1	a,	4,	1	, د	١,	1.
								а		a.		a.	a.	a.	a.	a.	a.	J.	J.	a.	a.	a.	J.	ı	ı	a.	а	а								



Accessories

470542	LED POWER SUPPLY , 20W, 24V
--------	-----------------------------

Notes		