

## GRAZIA PRO MAX FLEX-STRIP

## 24V 20mm 5m 13000lm 4000K

High lighting quality efficiently brought to the strip: the flexibly usable LED strips of the GRAZIA FLEXSTRIP family will impress you with their colour rendering index (CRI>90). The high luminous intensity combined with low power consumption (up to 110lm/W) is also an energy-saving plus. And thanks to the new variants, GRAZIA now offers you even better choice: several widths, luminous intensities and different light colours for outdoors and indoors, for private and commercial use. Benefit from lighting quality, a self-adhesive reverse and soldered cables, allowing each strip to be connected directly to a compatible 24V DC power supply. Each strip can be perfectly integrated into the Grazia profile system.

## **TECHNICAL DATA**

| Item no.:                   | 1004721       |
|-----------------------------|---------------|
| Nominal voltage             | 24V DC V      |
| Length                      | 500.0 cm      |
| Width                       | 2.0 cm        |
| Height                      | 0.15 cm       |
| Net weight                  | 0.238 kg      |
| Gross weight                | 0.255 kg      |
| IP Code                     | IP 20         |
| Safety class                | III           |
| Assembly                    | Surface       |
| Assembly details            | Ceiling, Wall |
| Lumen                       | 13000 lm      |
| Colour temperature          | 4000 Kelvin   |
| Beam angle                  | 120 °         |
| Color                       | white         |
| CRI                         | >90           |
| Binning                     | 3             |
| LED distance                | 0,5 cm        |
| Service life                | 30000 h       |
| Switching cycles            | 15000         |
| Minimum ambient temperature | -20 °C        |
| Maximum ambient temperature | 40 °C         |
|                             |               |

|    |    |     |   |   |    |    | 4  |    |    |    | 4 |   |   | 4 |    | 4  |    | -4 | 4 | 4 | 4 | ч | 4  | 4 | 4 | 4 | 4  |   |   |   |   |   |   |   |   |    |
|----|----|-----|---|---|----|----|----|----|----|----|---|---|---|---|----|----|----|----|---|---|---|---|----|---|---|---|----|---|---|---|---|---|---|---|---|----|
|    | a, | _1  |   | ä | a, | J. | J. | J. | a, | a, | J | J | J | J | ä  | ä  | ä  | ä  | ä |   |   |   |    |   |   |   |    |   |   |   |   |   |   |   |   |    |
| ı, | J  | ר ר | J | J | J  | J  | J  | J  | a, | a. | J | J | a | J | J  | J  | J  |    | 4 |   |   | J |    | ı |   | 1 | J. | 1 | ı | ı | 1 | ı | ı | L | 1 | ١, |
|    |    |     |   |   | п  |    |    | п  |    | 1  |   | 1 | 1 | п | Э. | Э. | Э. |    | п | 1 | 1 | п | а. | 1 | 1 | п | п  | т |   |   |   |   |   |   |   |    |



| BIG WHITE Page | 796 |
|----------------|-----|

## Accessories

| 470549 | LED POWER SUPPLY , 150W, 24V, incl. cable gland |
|--------|---|
|--------|---|

| Notes |  |  |
|-------|--|--|
|       |  |  |
|       |  |  |
|       |  |  |
|       |  |  |
|       |  |  |
|       |  |  |