## 





## PROFILE-STRIP X-SLIM 120

## 24V 4.8mm x 3 m, 3000K, 300lm/m

Extra-narrow LED strip in 3 m length for connection to a 24V DC power supply. The rear side is fitted with adhesive tape to make for simple installation. The strips come in several colours of light. To obtain constant light output over long lengths, the strips should be powered on both sides. For lengths in excess of 3 m, a new feed-in must be made.

## **TECHNICAL DATA**

| Item no.:                   | 552703       |
|-----------------------------|--------------|
| Nominal voltage             | 24V DC V     |
| Length                      | 300.0 cm     |
| Width                       | 0.5 cm       |
| Height                      | 0.2 cm       |
| Net weight                  | 0.035 kg     |
| Gross weight                | 0.085 kg     |
| IP Code                     | IP 20        |
| Safety class                | 111          |
| Assembly                    | Surface      |
| Assembly details            | Ceiling,Wall |
| Wattage                     | 6 W          |
| Lumen                       | 900 lm       |
| Colour temperature          | 3000 Kelvin  |
| Beam angle                  | 120 °        |
| CRI                         | >80          |
| Binning                     | 3            |
| LED distance                | 0,8 cm       |
| Service life                | 25000 h      |
| Switching cycles            | 12500        |
| Minimum ambient temperature | -20 °C       |
| Maximum ambient temperature | 50 °C        |
|                             |              |

Notes