



MALANG pendant

Master Version, LED, T16-R, 49 W

In addition to the clear and colour-changing LED light, the T5 ring tube provides basic illumination. The two light sources can be switched separately via external switches. To extend the MALANG master version we now offer slave devices. The synchronisation of these individual slave versions is made via the control signal from the master unit where a remote control is included. The package also includes a ceiling plate for direct mounting, one master or slave controller, and the remote control including batteries.

TECHNICAL DATA

| Item no.: | 147203 |
|-------------------------|-----------------|
| Socket | 2GX13 |
| Lamp | T16-R |
| Number of sockets | 1 |
| Lamps included | 0 |
| Primary nominal voltage | 230V ~50Hz mA/V |
| Pendant length | 150.0 cm |
| Net weight | 9.341 kg |
| Gross weight | 12.707 kg |
| IP Code | IP 20 |
| Safety class | 1 |
| Assembly | Surface |
| Assembly details | Ceiling |
| Wattage | 52 W |
| Color | grey |
| CRI | >80 |
| LXXBXX data | 70/50 |
| Service life | 20000 h |
| | |

Recommended lamp

| 548240 | RING TUBE T5 , fluorescent tube, 40- |
|--------|--------------------------------------|
| | W, 3000K |

Notes