



## **RIFFA**

## pendant, T16, silver-grey, max. 54W, dimmable

The shapely manufactured aluminium profile of our RIFFA pendant luminaire fits into any interior design, while the integrated dark light grid according to DIN standard guarantees a perfectly illuminated workstation with absolutely glare-free illumination properties. With the optionally available connection kit, numerous RIFFA pendant lights can be connected easily making your office or conference rooms more individual. Designed for the use of energy-saving and durable T5 fluorescent tubes, RIFFA pendant is supplied ready for direct connection to 230V mains supply.

## **TECHNICAL DATA**

| Item no.:               | 158304          |
|-------------------------|-----------------|
| Socket                  | G5              |
| Lamp                    | T16             |
| Number of sockets       | 1               |
| Lamps included          | 0               |
| Primary nominal voltage | 230V ~50Hz mA/V |
| Length                  | 120.0 cm        |
| Pendant length          | 150.0 cm        |
| Width                   | 7.0 cm          |
| Height                  | 8.0 cm          |
| Net weight              | 2.628 kg        |
| Gross weight            | 3.281 kg        |
| IP Code                 | IP 20           |
| Safety class            | I               |
| Assembly                | Surface         |
| Assembly details        | Ceiling         |
| Wattage                 | 54 W            |
| Color                   | grey            |
|                         | •               |

|    |     |     |   |    |    |   | 4 |    |    |    | 4 |   |    | 4  |    | 4  |    | 4  | 4  | 4 | 4 | ч | 4 | 4  | 4 | 4  | 4 |   |    |   |    |    |    |   |   |   |
|----|-----|-----|---|----|----|---|---|----|----|----|---|---|----|----|----|----|----|----|----|---|---|---|---|----|---|----|---|---|----|---|----|----|----|---|---|---|
|    | - 4 | - 4 |   | J. | J. | J | J | J  | J. | a, | J | J | J  | J  | J, | a, | ä  | a, | J, |   |   |   |   |    |   |    |   |   |    |   |    |    |    |   |   |   |
| ı, | L   | l l | J | J  | 1  | J | J | J. | 4  | ä  | J | J | a, | J  | ä  | J  | ä  |    | 4  |   |   | J |   | J. |   | ı  | J | ı | J. | J | J. | ١, | ١, | 1 | ı | ı |
|    |     |     |   |    | 4  |   |   |    |    | 4  |   | 1 | 1  | -1 | 1  | 1  | а. | 1  | 1  | 1 | 1 | 1 | 1 | 1  | 1 | т. | 4 | 1 |    |   |    |    |    |   |   |   |



## Accessories

| 158320 | LONG CONNECTOR , for RIFFA, silver-grey |
|--------|---|
|--------|---|

| otes |  |
|------|--|
|      |  |
|      |  |
|      |  |
|      |  |
|      |  |
|      |  |
|      |  |
|      |  |
|      |  |