



WAVE 25

pendant, LED, 2000K-3000K Dim to Warm, aluminium/white

The WAVE 25, available in black, white, brass, or brushed aluminium, has an elegant wave design. Equipped with one powerful, warm white premium COB LED, as well as LED driver included in the scope of supply, the set can be used in any lighting situation. The pendant length of the WAVE 25 can be adjusted using the wire fixer. The lighting atmosphere can be adjusted in an uncomplicated way using the dim-to-warm function.



TECHNICAL DATA

| | |
|-------------------------------------|------------------------|
| Item no.: | 1000644 |
| Primary nominal voltage | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 250 mA/V |
| Length | 26.5 cm |
| Pendant length | 150.0 cm |
| Width | 11.4 cm |
| Height | 7.2 cm |
| Net weight | 1.197 kg |
| Gross weight | 1.579 kg |
| IP Code | IP 20 |
| Safety class | I |
| Assembly | Surface |
| Assembly details | Ceiling |
| Dimming technology | trailing edge |
| Wattage | 12 W |
| Lumen | 440 lm |
| Colour temperature | 2000-3000 Kelvin |
| Beam angle | 100 ° |
| Color | aluminium |
| CRI | >90 |
| Binning | 6 |
| LXXBXX data | 70/50 |



| | |
|--------------|---------|
| Service life | 30000 h |
|--------------|---------|

Notes
