## ........... а. J J . . . . . . . ы a. л. л . . ........... L J . . . . . . . . . . . ы Л . . . . . . . . . . . . . . . . . . л






## **OPEN GRILL LED**

## double twist pendant, square, black

The OPEN GRILL is a professional pendant for surface mounting. Within its rectangular frame there are eight LEDs each with 7.5W of power. Both rotating elements make the luminaire so special. The OPEN GRILL pendant is suitable for direct connection to the 230V mains supply.



## **TECHNICAL DATA**

Item no.:	1001295
Lamps included	0
Number of different light outlets	1
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	1050 mA/V
Vertical tilting range	270 °
Length	73.0 cm
Pendant length	200.0 cm
Width	72.0 cm
Height	4.5 cm
Net weight	4.807 kg
Gross weight	6.502 kg
IP Code	IP 20
Safety class	1
Assembly	Surface
Assembly details	Ceiling,Wall
Wattage	54 W
Lumen	4500 lm
Colour temperature	3000 Kelvin
Beam angle	120 °
Color	black
CRI	>80



Binning	3
LXXBXX data	70/50
Service life	30000 h
BIG WHITE Page	172

Notes

Last updated 2021-01-22 13:26:41 | Subject to technical changes