




Q-LINE SINGLE LED

pendant, 1500mm, black

The Q-LINE wall light is available with a choice of a white, back, or silver-grey luminaire housing. A diffuser made of acrylic glass found underneath provides glare-free lighting properties. The integrated warm-white LEDs give an output of 3200 lm. Due to the integrated LED driver, the luminaire can be directly connected to the 230V mains supply.



TECHNICAL DATA

| Item no.: | 1001306 |
|-------------------------------------|------------------------|
| Lamps included | 0 |
| Number of different light outlets | 1 |
| Primary nominal voltage | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 700 mA/V |
| Length | 142.0 cm |
| Pendant length | 200.0 cm |
| Width | 6.0 cm |
| Height | 6.0 cm |
| Net weight | 3.343 kg |
| Gross weight | 3.872 kg |
| IP Code | IP 20 |
| Safety class | 1 |
| Assembly | Surface |
| Assembly details | Ceiling |
| Wattage | 45.8 W |
| Lumen | 3700 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 120 ° |
| Color | black |
| CRI | >80 |
| UGR≤ | 28 |
| | |



| Binning | 3 |
|----------------|---------|
| Binning 2 | 3 |
| LXXBXX data | 70/50 |
| Service life | 30000 h |
| Service life 2 | 30000 h |
| BIG WHITE Page | 169 |

Notes