



AROSA

1,25m, TRIAC PD, LED indoor pendant, white, 3000K

The AROSA pendant, available in two lengths, is equipped with white, black or anodised aluminium housing as desired. A PMMA diffuser, which is used on the upper and lower light outlet, provides glare-free lighting characteristics. The integrated warm-white LEDs provide a high degree of light output. Thanks to the TRIAC dimmable LED driver, the luminaire can be directly connected to the 230 Volt mains voltage supply.

TECHNICAL DATA

Item no.:	1001941
Number of different light outlets	2
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	500 mA/V
Length	125.3 cm
Pendant length	200.0 cm
Width	2.7 cm
Height	4.2 cm
Net weight	2.287 kg
Gross weight	3.052 kg
IP Code	IP 20
Safety class	I
Assembly	Surface
Assembly details	Ceiling
Dimming technology	trailing edge
Wattage	32 W
Lumen	1700 lm
Colour temperature	3000 Kelvin
Beam angle	110 °
Color	white
CRI	>80
Binning	3



Binning 2	3
LXXBXX data	70/50
Service life	40000 h
Service life 2	40000 h
Ambient temperature	25 °C
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
BIG WHITE Page	111

Notes
