


## AROSA

### 2m, TRIAC PD, LED indoor pendant, white, 3000K

The AROSA pendant, available in two lengths, is equipped with white, black or anodised aluminium housing as desired. A PMMA diffuser, which is used on the upper and lower light outlet, provides glare-free lighting characteristics. The integrated warm-white LEDs provide a high degree of light output. Thanks to the TRIAC dimmable LED driver, the luminaire can be directly connected to the 230 Volt mains voltage supply.



## TECHNICAL DATA

Item no.:	1001944
Number of different light outlets	2
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	600 mA/V
Length	200.3 cm
Pendant length	200.0 cm
Width	2.7 cm
Height	4.2 cm
Net weight	3.181 kg
Gross weight	4.198 kg
IP Code	IP 20
Safety class	I
Assembly	Surface
Assembly details	Ceiling
Dimming technology	trailing edge
Wattage	65 W
Lumen	3600 lm
Colour temperature	3000 Kelvin
Beam angle	110 °
Color	white
CRI	>80
Binning	3



<b>Binning 2</b>	3
<b>LXXBXX data</b>	70/50
<b>Service life</b>	40000 h
<b>Service life 2</b>	40000 h
<b>Ambient temperature</b>	25 °C
<b>Minimum ambient temperature</b>	-20 °C
<b>Maximum ambient temperature</b>	35 °C
<b>BIG WHITE Page</b>	111

## Notes

---

---

---

---

---