а. J J з з . л Л ГГ 1 л





SUPROS PD

Indoor LED pendant, round, white, 3000K, 60° reflector, CRI90, 2600Im

The SUPROS light series impresses with its multitude of possible applications, excellent LED technology and its harmonious design. With its very high luminous flux, the SUPROS product family is ideally suited to replace power-hungry, conventional lighting installations. The wide-area reflector included in the delivers can be replaced by reflectors with narrower beam angles which are optionally available. This can be done without the need for tools. With the factory-installed LED driver, all the luminaires in the series are suitable for direct connection to the 230V mains supply.

TECHNICAL DATA

Item no.:	1003276
Lamps included	0
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	750 mA/V
Pendant length	200.0 cm
Height	18.5 cm
Diameter	12.7 cm
Net weight	1.633 kg
Gross weight	1.764 kg
IP Code	IP 20
Safety class	l
Assembly	Surface
Assembly details	Ceiling
Wattage	31 W
Lumen	2600 lm
Colour temperature	3000 Kelvin
Beam angle	60 °
Color	white
CRI	>90
Binning	3
LXXBXX data	70/50
Service life	50000 h



Ambient temperature	25 °C
BIG WHITE Page	179

114102REFLECTOR , for SUPROS, 20°, incl.
glass and fixing ring114104REFLECTOR , for SUPROS, 40°, incl.
glass and fixing ring

Accessories

Notes