



HELIA 60

pendant, LED, 3000K, round, brushed copper, flat canopy, 7.5W

With the HELIA 60 you have a recessed pendant with a puristic and clear design. This luminaire is available in black, white and brushed copper. With integrated 7.5 W warm-white premium LED. The luminaire is supplied with a 1.5 m connection lead / suspension. A separate 500mA constant current driver is required for operation.

TECHNICAL DATA

Item no.:	158409
Lamps included	0
Number of different light outlets	1
Secondary power / secondary voltage	500 mA/V
Length	60.0 cm
Pendant length	150.0 cm
Diameter	3.0 cm
Installation diameter	6.8 cm
Installation depth	3.0 cm
Net weight	0.483 kg
Gross weight	0.738 kg
IP Code	IP 20
Safety class	III
Assembly	Recessed
Assembly details	Ceiling
Wattage	7.5 W
Lumen	550 lm
Colour temperature	3000 Kelvin
Beam angle	40 °
Color	copper
CRI	>90
Binning	6

Accessories

464091	LED DRIVER , 9VA, 500mA, incl. strain relief
464144	LED DRIVER , 15W, 500mA, incl. strain relief, dimmable

LXXBXX data	70/50
Service life	30000 h
Maximum ambient temperature	30 °C

Notes
