




AKALO 83

DL, indoor recessed ceiling light, 3000K 4200K 5700K adjustable, white

The AKALO luminaire is a recessed ceiling light for universal use indoors. The light temperature is switchable in all versions. The electrical connection is made directly to the 230V mains supply.



TECHNICAL DATA

Item no.:	1001264
Lamps included	0
Number of different light outlets	1
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	120 mA/V
Height	6.5 cm
Diameter	11.0 cm
Installation diameter	9.2 cm
Installation depth	7.0 cm
Net weight	0.21 kg
Gross weight	0.27 kg
IP Code	IP 20
Safety class	II
Impact resistance class	IK02
Impact resistance	0,200000000000000001 Joule
Assembly	Recessed
Assembly details	Ceiling
Dimming technology	trailing edge
Number of through-wires	0
Wattage	9 W
Lumen	800 / 880 / 850 lm
Colour temperature	3000/4200/5700 Kelvin



Beam angle	90 °
Color	white
CRI	>80
UGR ≤	28
Binning	6
LXXBXX data	70/50
Service life	30000 h
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
BIG WHITE Page	406

Notes
