



## SLV Play

**LED indoor recessed ceiling light, nickel, 2700-6500K**

The PLAY Downlight CCT nickel LED recessed spot from SLV is more than a typical light source. The recessed light not only lightens your environment but also enriches far more, can be adjusted to the current mood in an inimitable way, creating a unique lighting experience. Enjoy the highest level of user convenience: When it is used with the Amazon Alexa and the Google Home System, the recessed light is right at the cutting edge. This way or that, users have the choice of whether they want to control the various scenarios by voice, via app, with the remote control which can be purchased separately, or classically via light switch. Stay flexible. You want to know a bit more? Gladly. SLV PLAY Downlight CCT nickel is excellent proof of the fact that modern lighting conditions and impressive energy efficiency are not mutually exclusive. Based on a stylish design and comfortable colour scheme, you profit from the ability to tilt the model up to a 38° beam angle. You therefore have the opportunity to make targeted use of the bandwidth of the 64,000 shades of white (2700 to 6500 Kelvin) in each room. The fixed premium LED is found behind the matt glass diffuser. The emphasis has also been placed on having bright but glare-free light with this model. Therefore, nothing stands in the way of using the light in a wide variety of living areas. And last but not least, long-term use is guaranteed thanks to the service life of 25,000 hours. A hub, a bridge or a gateway are not required. A WLAN signal is required for full usability. You can look forward to your product with the customary SLV quality!

## TECHNICAL DATA

Item no.:	1002527
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	75 mA/V
Nominal voltage	220-240V ~50/60Hz V
Vertical tilting range	50 °
Vertical tilting range	25 °
Vertical tilting range	-25 °
Height	4.5 cm
Diameter	10.9 cm
Installation diameter	8.4 cm
Net weight	0.275 kg
Gross weight	0.363 kg
IP Code	IP 20
Safety class	II
Assembly details	Ceiling
Energy efficiency index	A
Wattage	10 W
Lumen	450 lm
Beam angle	38 °
Color	stainless steel
CRI	80
Binning	6

## Accessories

1002516	SLV Play remote control
---------	-------------------------

<b>Binning</b>	6
<b>Binning 2</b>	6
<b>LXXBXX data</b>	70/50
<b>Service life</b>	25000 h
<b>Service life</b>	25000 h
<b>Switching cycles</b>	50000
<b>Start-up time</b>	0,5 s
<b>Minimum ambient temperature</b>	-20 °C
<b>Maximum ambient temperature</b>	35 °C

## Notes

---

---

---

---

---