


RENISTO DL

LED indoor recessed ceiling light, angular, white, 3000K, $36^{\circ},\,9.6W$

The simplicity and effectiveness of the innovative RENISTO DL system recessed fitting is captivating. Available in square and round designs as well as three sizes, all versions are equipped with powerful, warm white LEDs. The products in the RENISTO DL system can be combined in a myriad of ways with suitable interior covers. The electrical connection is made directly to the 230V mains supply.



TECHNICAL DATA

| Item no.: | 1001828 | | |
|-------------------------------------|------------------------|--|--|
| Primary nominal voltage | 220-240V ~50/60Hz mA/V | | |
| Secondary power / secondary voltage | 500 mA/V | | |
| Vertical tilting range | 30 ° | | |
| Horizontal rotation range | 350 ° | | |
| Length | 8.5 cm | | |
| Width | 8.5 cm | | |
| Height | 6.7 cm | | |
| Installation diameter | 7.5 cm | | |
| Installation depth | 7.0 cm | | |
| Net weight | 0.24 kg | | |
| Gross weight | 0.302 kg | | |
| IP Code | IP 20 | | |
| Safety class | Ш | | |
| Assembly | Recessed | | |
| Assembly details | Ceiling | | |
| Dimming technology | Leading edge | | |
| Wattage | 9.6 W | | |
| Lumen | 500 lm | | |
| Colour temperature | 3000 Kelvin | | |
| Beam angle | 36 ° | | |
| Color | white | | |
| | • | | |





| CRI | >80 |
|--------------|---------|
| Binning | 5 |
| LXXBXX data | 70/50 |
| Service life | 30000 h |

| Notes | | | |
|-------|--|--|--|
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |