4 л л. ы а л. ы л a a secondara a L Л ы гг ы л







OCCULDAS 14

recessed fitting, LED, 3000K, indirect, white, 15W

The OCCULDAS 14 dimmable recessed ceiling light was designed exclusively by David Morgan and is fitted with a 15W premium LED. The central trim ensures homogeneous, glare-free, atmospheric indirect lighting. Thanks to the built-in LED driver, the luminaire is suitable for direct connection to a 230V mains supply. The OCCULDAS series is available in other variants.





TECHNICAL DATA

Item no.:	117331
Lamps included	0
Number of different light outlets	1
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	350 mA/V
Height	3.8 cm
Diameter	14.0 cm
Installation diameter	13.0 cm
Installation depth	3.7 cm
Net weight	0.44 kg
Gross weight	0.621 kg
IP Code	IP 20
Safety class	II
Assembly	Recessed
Assembly details	Ceiling
Dimming technology	trailing edge
Wattage	15 W
Lumen	810 lm
Colour temperature	3000 Kelvin
Beam angle	120 °
Color	white
CRI	>80



Binning	6
LXXBXX data	70/50
Service life	25000 h
BIG WHITE Page	411

Notes

Last updated 2021-01-22 13:26:41 | Subject to technical changes