


## CRYSTAL DL

LED indoor recessed ceiling light, clear, 1800-3000K

With the CRYSTAL LED recessed fitting we are providing you with, a recessed fitting made from crystal glass which creates various prismatic effects because of the halogen bulb that is used. To operate the recessed fitting, a matching transformer with 12V alternating current is required.



## TECHNICAL DATA

|                                     |                             |
|-------------------------------------|-----------------------------|
| Item no.:                           | 1002120                     |
| Primary nominal voltage             | 220-240V ~50/60Hz mA/V      |
| Secondary power / secondary voltage | 350 mA/V                    |
| Height                              | 5.2 cm                      |
| Diameter                            | 9.0 cm                      |
| Installation diameter               | 6.0 cm                      |
| Installation depth                  | 6.0 cm                      |
| Net weight                          | 0.37 kg                     |
| Gross weight                        | 0.45 kg                     |
| IP Code                             | IP 20                       |
| Safety class                        | II                          |
| Assembly                            | Recessed                    |
| Assembly details                    | Ceiling                     |
| Dimming technology                  | Leading edge, trailing edge |
| Wattage                             | 7.3 W                       |
| Lumen                               | 460 lm                      |
| Colour temperature                  | 1800-3000 Kelvin            |
| Beam angle                          | 38 °                        |
| Color                               | transparent                 |
| CRI                                 | >95                         |
| Binning                             | 3                           |
| LXXBXX data                         | 70/50                       |



|              |         |
|--------------|---------|
| Service life | 30000 h |
|--------------|---------|

**Notes**

---

---

---

---

---