



DORENO

round, white, 75°, 4000K

The simplicity and effectiveness of the innovative DORENO downlight is captivating. It is available in 3000K and 4000K. Equipped with a powerful, warm white LED, the downlight can be used in any lighting situation. The electrical connection is made using an exclusive LED driver.

TECHNICAL DATA

Item no.:	1000310
Secondary power / secondary voltage	70010001050 mA/V
Height	10.9 cm
Diameter	26.0 cm
Installation diameter	17.5 cm
Installation depth	16.0 cm
Net weight	0.883 kg
Gross weight	1.254 kg
IP Code	IP 20
Safety class	III
Assembly	Recessed
Assembly details	Ceiling, Ceiling with Acc.
Wattage	29 W
Lumen	3000 lm
Colour temperature	4000 Kelvin
Beam angle	75 °
Color	white
CRI	>80
Binning	6
LXXBXX data	70/50
Service life	25000 h

Accessories

1001267	LED driver , 700mA, 40W, TRIAC dimmable
464032	TCI LED DRIVER , 50VA, 350-1050mA, dip switch, incl. strain relief, DALI dimmable
464168	LED DRIVER , 40W, 700mA, incl. strain relief
464174	LED DRIVER , 40W, 700mA, incl. strain relief, dimmable

Notes
