

NIMA recessed fitting

round, white, 10W, 3000K

The NIMA recessed light made from aluminium is available in matt white or silver-grey finish, as well as with round or square shade. The 120° beam angle of the fixed, Premium LED module provides a broad and uniform base illumination. A suitable constant current driver providing 350mA is required to operate the recessed fitting.

TECHNICAL DATA

Item no.:	1000276
Secondary power / secondary	350 mA/V
voltage	
Height	3.0 cm
Diameter	18.0 cm
Installation diameter	17.2 cm
Installation depth	4.0 cm
Net weight	0.413 kg
Gross weight	0.562 kg
IP Code	IP 20
Safety class	III
Assembly	Recessed
Assembly details	Ceiling
Wattage	10 W
Lumen	560 lm
Colour temperature	3000 Kelvin
Beam angle	120 °
Color	white
CRI	>80
Binning	6
LXXBXX data	70/50
Service life	30000 h
	1

						4				4			4		-		4	-	4	-	-	-	-	4	4	4									
	4	4	4	a,	J	4	J	J	a,	J	J	J	J	J	a,	a,	a,	a,																	
J	1 4		J	ı	J	J	J.	J	4	J.	J	J	J	ä	J	J		a.			J		1		4	4	1	J.	ı	1	١,	1	u	4	
				ă.			ы		а		я	a.	ы	a.	л	a.	J.	J.	J.	a.	a.	a.	_	ı	a.	а	а								



Accessories

1002803	LED driver , 9.1 - 15W 350mA, dim- mable

Notes			